10K CAST IRON ,BALL VALVES

Fig : 10-FBF-N-L/470L
Sizes : 1/2～8inch(15～200mm)
FULL BORE,FLANGED ENDS.
Standards :
・End to End : MANUFACTURER STANDARD
・End Connection : JIS B2239 10K
・Wall Thickness : MANUFACTURER STANDARD
Test Standard : KITZ St'd-2
Approvals : 1/2～8inch(15～200mm)
Standards : 1/2～8inch(15～200mm)





Dimensions

SIZE(inch/mm)		L	H	D	Approx (kg)
1/2	15	110.0	102.0	130.0	2.6
3/4	20	120.0	105.0	130.0	3.2
1	25	130.0	124.0	160.0	5.0
11/4	32	140.0	128.0	160.0	6.7
11/2	40	165.0	114.0	230.0	8.0
2	50	180.0	121.0	230.0	10
21/2	65	190.0	154.0	400.0	17
3	80	200.0	163.0	400.0	20
4	100	230.0	199.0	460.0	31
5	125	300.0	219.0	460.0	45
6	150	340.0	292.0	1000.0	70
8	200	450.0	352.0	1500.0	111

Material

Part Name	Material	Remark
BODY	CAST IRON	A126 CL.B
BODY CAP	CAST IRON	A126 CL.B
STEM	STAINLESS STEEL	403SS
BALL	STAINLESS STEEL	304SS

Specifications

10K CAST IRON,BALL VALVES
End Connection : JIS B2239 10K,Sizes : 1/2～8inch(15～200mm),
BODYMaterial:CAST IRON, BODY CAPMaterial:CAST IRON,
STEMMaterial:STAINLESS STEEL, BALLMaterial:STAINLESS STEEL,KITZ Fig : 10-FBF-N-L/470L

※Images are for illustrative purposes only. The actual product may differ.

※For details, please refer to the submitted drawing.

Fig Detail Page

Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.