10K DUCTILE IRON ,BUTTERFLY VALVES

Fig : 10L2-N-UEL/562-UESG
Sizes : 2～24inch(50～600mm)
GEAR OPERATED. DEW CONDENSATION PREVENTING.
Standards :
・End to End : JIS B2032 46 SERIES
・End Connection : WAFER TYPE (JIS 5K,10K)
・Wall Thickness : MANUFACTURER STANDARD
Test Standard : KITZ St'd-4
Approvals : 2～24inch(50～600mm)
Standards : 2～24inch(50～600mm)





Dimensions

SIZE(inch/mm)		L	H	D	Approx (kg)
2	50	43.0	220.0	110.0	2.7
21/2	65	46.0	228.0	110.0	3.0
3	80	46.0	248.0	110.0	3.8
4	100	52.0	258.0	110.0	4.2
5	125	56.0	286.0	110.0	6.4
6	150	56.0	298.0	110.0	7.7
8	200	60.0	409.0	170.0	15
10	250	68.0	477.0	250.0	29
12	300	78.0	502.0	250.0	37
14	350	78.0	571.0	310.0	68
16	400	102.0	626.0	310.0	83
18	450	114.0	650.0	310.0	109
20	500	127.0	745.0	360.0	155
24	600	154.0	793.0	360.0	250

Material

Part Name	Material	Remark
BODY	DUCTILE IRON	A536 Gr.65-45-12
STEM	STAINLESS STEEL	A276 TYPE410
SEAT RUBBER(4)	EPDM	

Specifications

10K DUCTILE IRON,BUTTERFLY VALVES
End Connection : WAFER TYPE (JIS 5K,10K),Sizes : 2～24inch(50～600mm),
BODYMaterial:DUCTILE IRON, STEMMaterial:STAINLESS STEEL, SEAT
RUBBER(4)Material:EPDM,KITZ Fig : 10L2-N-UEL/562-UESG

※Images are for illustrative purposes only. The actual product may differ.

※For details, please refer to the submitted drawing.

Fig Detail Page

Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.