PN16 CAST IRON ,Y TYPE STRAINERS

Fig : EAEN16-FTF<GA101>/530AF
Sizes : 2～20inch(50～500mm)
BOLTED COVER,FLANGED ENDS.
Standards :
・End to End : EN558 PN16 SERIES 1
・End Connection : EN 1092-2 PN16
・Wall Thickness : MANUFACTURERS STANDARD
Test Standard : KITZ St'd-1
Approvals : 2～20inch(50～500mm)
Standards : 2～20inch(50～500mm)





Dimensions

SIZE(inch/mm)		L	H	D	Approx (kg)
2	50	230.0	158.0	0.0	-
21/2	65	290.0	176.0	0.0	-
3	80	310.0	199.0	0.0	-
4	100	350.0	240.0	0.0	-
5	125	400.0	292.0	0.0	-
6	150	480.0	320.0	0.0	-
8	200	600.0	399.0	0.0	-
10	250	730.0	517.0	0.0	-
12	300	850.0	568.0	0.0	-
14	350	980.0	642.0	0.0	-
16	400	1100.0	750.0	0.0	-
18	450	1200.0	784.0	0.0	-
20	500	1250.0	857.0	0.0	-

Material

Part Name	Material	Remark
BODY	CAST IRON	EN-GJL250
COVER	CAST IRON	EN-GJL250

Specifications

PN16 CAST IRON,Y TYPE STRAINERS
End Connection : EN 1092-2 PN16,Sizes : 2～20inch(50～500mm),
BODYMaterial:CAST IRON, COVERMaterial:CAST IRON,KITZ Fig : EAEN16-FTF<GA101>/530AF

※Images are for illustrative purposes only. The actual product may differ.

※For details, please refer to the submitted drawing.

Fig Detail Page

Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.