PN25 DUCTILE IRON ,Y TYPE STRAINER

Fig : (PHOX)EN25-DTF/678E
Sizes : 2～12inch(50～300mm)
BOLTED COVER,FLANGED ENDS.
Standards :
・End to End : EN 558-1 Series4
・End Connection : EN 1092-2 PN25
・Wall Thickness : MANUFACTURERS STANDARD
Test Standard : KITZ St'd-1
Approvals : 2～12inch(50～300mm)
Standards : 2～12inch(50～300mm)





Dimensions

SIZE(inch/mm)		L	H	D	Approx (kg)
2	50	216.0	140.0	0.0	-
21/2	65	241.0	162.0	0.0	-
3	80	283.0	184.0	0.0	-
4	100	305.0	225.0	0.0	-
5	125	381.0	280.0	0.0	-
6	150	403.0	318.0	0.0	-
8	200	521.0	405.0	0.0	-
10	250	635.0	485.0	0.0	-
12	300	749.0	580.0	0.0	-

Material

Part Name	Material	Remark
BODY	DUCTILE IRON	EN1563 EN-GJS-450
COVER	DUCTILE IRON	EN1563 EN-GJS-450

Specifications

PN25 DUCTILE IRON,Y TYPE STRAINER
End Connection : EN 1092-2 PN25,Sizes : 2～12inch(50～300mm),
BODYMaterial:DUCTILE IRON, COVERMaterial:DUCTILE IRON,KITZ Fig :
(PHOX)EN25-DTF/678E

※Images are for illustrative purposes only. The actual product may differ.

※For details, please refer to the submitted drawing.

Fig Detail Page

Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.